

Self –Powered Autonomous Device for Wireless Structural Health Monitoring

Matthew Pearson - pearsonmr@cardiff.ac.uk












Motivation

Wireless SHM for aerospace applications

Project Aims

- Develop EH and power management solution to power a SHM system
- Investigate the use of:
 - Thermoelectric
 - Piezoelectric
 - RF power delivery
- Develop a multiple input power management solution








Motivation

 Wireless SHM for aerospace application

Project Aims

- Develop EH and power management solution to power a SHM system
- Investigate the use of:
 - Thermoelectric
 - Piezoelectric
 - RF power delivery
- Develop a multiple input power management solution









Key Achievements

- Assessed performance of commercial TEGs
- Typical positive and negative aircraft gradients up to 30°C
- Developed optimisation programme for placement of piezoelectric vibration harvesters
- Feasibility study into developing power delivery system utilising reversed RF power amplifiers
- Developed multiple input power management system using charge transfer circuit









Conclusions

- For aircraft temperature gradients:
 - TEG power levels from 13-45mW
- Significant increased piezoelectric harvested power
 - Doubled average power levels over the frequency bandwidth
- Feasible to reverse RF power amplifier to generate power delivery system
 - Able to receive 200mW
- Developed power management system for multiple input using charge transfer circuit









Future Work

- Successfully led to TSB grant project:
 - Montagu a continuation of Sandwich project
 - Aim is to fully develop a lightweight, miniaturised power management solution for autonomous SHM systems
- Further work ongoing on another
 TSB grant entitled Sentient
 - Aim to develop low power SHM system







